


SERIE: LC1562-RC-40K-20-AC

CODE YLD: 021208



ALUMINIO
ALUMINIUM
ALUMINIUM



CLASE 1
CLASS 1
CLASSE 1



CE APROBADO
CE APPROVED
CE APPROUVÉ



ROHS APROBADO
ROHS APPROVED
ROHS APPROUVÉ

INFORMACIÓN BÁSICA/BASIC INFORMATION/INFORMATION DE BASE

INSTALACIÓN

Carril trifásico

MATERIAL

Aluminio

ACABADO

Cobre Brillante

USO

Interior

GARANTÍA

3 Años

INSTALLATION

Three-phase rail

MATERIAL

Aluminium

FINISH

Bright Copper

USE

Indoor

WARRANTY

3 Years

INSTALLATION

Rail triphasé

MATÉRIEL

Aluminium

FINITION

Cuivre Brillant

UTILISER

À L'Intérieur

GARANTIE


3 Ans

INFORMACIÓN TÉCNICA/TECHNICAL INFORMATION/INFORMATION TECHNIQUE


Datos lumínicos/Light data/Données lumineuses

Temperatura de color/Color temperature/Température de couleur	4000 K
Indice reproducción cromática/Color rendering index/Indice de rendu des couleurs	>97
Lúmenes/lumens	1510 lm
Eficiencia lumínica/Light efficiency/Efficacité lumineuse	76 lm/w
Óptica/Optics/Optique	Simétrica/Symmetrical/Symétrique
Ángulo de apertura/Beam angle/Angle d'ouverture	38°
Orientable/Adjustable/Ajustable	Si/Yes/Oui
Vida útil/Useful life/Durée de vie	L80 50.000H
UGR	<19

Fotometría Polar/polar photometry/photométrie polaire



Fotometría cónica/Cone photometry/Photométrie conique





Datos eléctricos/Electrical data/Données électriques

Potencia/Power/Puissance	20W
Tensión/Voltage/Tension	220-240V AC
Frecuencia/Frequency/Fréquence	50-60 Hz
Control de regulación/Regulation control/Contrôle de régulation	-
Driver	KGP
Salida del driver/Driver output	500mA
LED	BRIDGELUX
Clase de aislamiento/Insulation class/Classe d'isolation	I
Clasificación energética/Energy classification/Classement énergétique	A+

Datos mecánicos/Mechanical data/Données mécaniques

Temperatura funcionamiento/Operating temperature/Température de fonctionnement	-20°C+40°C
Accesorios/Accessories/Accessoires	-
Dimensiones/Dimensions	L170XW167XH100
Dimensiones de corte/Cutting dimensions/Dimensions de coupe	-
Peso/Weight/Poids	0,975 Kg
Protección IP/IP Protection	IP20

EMBALAJE/PACKAGING / EMBALLAGE

	CAJA/BOX/ BOÎTE	CARTON
MEDIDAS/SIZE/MEASURES	L170XW110XH210 mm	L450XW360XH240 mm
PESO/WEIGHT/POIDS	0,975 Kg	8,900 Kg
UNIDADES/UNITS/UNITÉS	1	8