



Ficha técnica/Data sheet/Fiche technique



SERIE: UFO EFFICIENT 200W 5700K 120

CODE: E8-5540 / 035540



ALUMINIO
ALUMINIUM
ALUMINIUM



CLASE 1
CLASS 1
CLASSE 1



CE APROBADO
CE APPROVED
CE APPROUVÉ




ROHS APROBADO
ROHS APPROVED
ROHS APPROUVÉ



PROTECCIÓN
PROTECTION
PROTECTION



ÍNDICE DE PROTECCIÓN IK
IK PROTECTION INDEX
INDICE DE PROTECTION IK




INFORMACIÓN BÁSICA/BASIC INFORMATION/INFORMATION DE BASE

INSTALACIÓN	INSTALLATION	INSTALLATION
Suspendida	Suspended	Suspendu
MATERIAL	MATERIAL	MATÉRIEL
Aluminio	Aluminium	Aluminium
ACABADO	FINISH	FINITION
Negro	Black	Noir
USO	USE	UTILISER
Interior/Exterior	Indoor/Outdoor	À L'Intérieur/Extérieur
GARANTÍA	WARRANTY	GARANTIE
5 Años	5 Years	5 Ans


Datos lumínicos/Light data/Données lumineuses

Temperatura de color/Color temperature/Température de couleur	5700 K
Índice reproducción cromática/Color rendering index/Indice de rendu des couleurs	>70
Lúmenes/lumens	30.000 lm
Eficiencia lumínica/Light efficiency/Efficacité lumineuse	150 lm/w
Óptica/Optics/Optique	Translúcida
Ángulo de apertura/Beam angle/Angle d'ouverture	120°
Orientable/Adjustable/Ajustable	No/Not/Ne pas
Grados de orientación/Orientation degress/Degrés d'orientation	-
Vida útil/Useful life/Durée de vie	L70 50.000H

Fotometría Polar/polar photometry/photométrie pola



Fotometría cónica/Cone photometry/Photométrie conique





Datos eléctricos/Electrical

Potencia/Power/Puissance	200W
Tensión/Voltage/Tension	100-240V AC
Frecuencia/Frequency/Fréquence	50-60 Hz
Factor de potencia/Power factor/Facteur de puissance	>0,97
Control de regulación/Regulation control/Contrôle de régulation	
Driver	MOSO
LED	LUMILEDS 2835
Clase de aislamiento/Insulation class/Classe d'isolation	I
Clasificación energética/Energy classification/Classement énergétique	C

Datos mecánicos/Mechanical data/Données mécaniques

Temperatura funcionamiento/Operating temperature/Température de fonctionnement	-30°C+50°C
Accesorios/Accessories/Accessoires	
Dimensiones producto/Recessed dimensions/dimensions de produit	Ø3100 x 142 mm
IK	IK08
IP	IP65

EMBALAJE/PACKAGING / EMBALLAGE

CAJA/BOX/ BOÎTE

MEDIDAS/SIZE/MEASURES

PESO/WEIGHT/POIDS

UNIDADES/UNITS/UNITÉS

1